

# SP-SR2

## Surround



### COMPACT DIMENSIONS

The SP-SR2 was developed for 5.1/7.1 surround and integrates nicely thanks to its compact form.



### EASY MOUNT

Two recessed hangers allow flush and easy mounting on the wall. There's also space for cable loops.



### CABLE CUTOUT

The SP-SR1 has a cable cutout on the top for simple setup when forced to change speaker placement.

- **Passive, 2-Way Surround Loudspeaker**
- **2 x 4" + 1.1" Soft Dome Tweeter**
- **100W/200W (AES/Program)**
- **100 x 100° Dispersion**
- **Extremely compact**

### DESCRIPTION

*The SP-SR2 is a very compact passive 2-way surround loudspeaker for traditional 5.1/7.1 cinema applications. Installation is as easy as hanging a picture with two hangers on a wall. The wiring terminal is hidden and recessed on the rear side of the cabinet. There is also space for the excessive cable. In case the speakers are for retrofitting into existing rooms it boasts an almost invisible cutout on the top of the cabinet so the existing wires can be routed to the perfect position on-wall.*

*Additionally wiring complexity can be minimised as it can easily be daisy-chained with its 16 Ohm impedance.*

*the real*  
**CINEMA SOUND**  
*sensation.*

# SP-SR2



## TECHNICAL SPECIFICATIONS

Frequency Response	100 – 19'000 Hz
Sensitivity (SPL 1W/m)	89 dB
Nominal Impedance	16 $\Omega$
Dispersion (H x V)	100 x 100°
Power Handling (AES/Program/Peak)	100W / 200W / 400W
System	Passive, 2-Way, Fullrange
LF Driver	2 x 4"
HF Driver	1.1" Soft Dome Tweeter
Terminal	Spring-loaded
Dimensions ( B x H x T )	275 x 275 x 172 mm
Net Weight	5 kg

## TECHNICAL DRAWING

